

Amendments to the Specification

Please make the following amendment to paragraph 1 on page 5, line 6:

Referring to Figs. 1-3, a sexual aid device according to the present invention is generally designated by the numeral 10. The device 10 comprises a large plastic housing 11 which may be made of 2 pieces. This plastic housing 11 is then sheathed in a silicon sleeve or overmold 13. As shown, the sexual aid device 10 includes a first curved portion 12 and a second substantially straight elongated portion 14 that extends coextensively from the curved portion 12 forming an approximate J shape. The curved portion 12 is adapted to be inserted within the vagina, although it may be inserted within the anus. Preferably, the distal tip 16 of the curved portion 12 is shaped like a male penis. However, of course, the distal tip 16 may be structured to have other shapes. The curved portion 12 and the substantially straight portion 14 are structured and arranged such that when the curved portion 12 is inserted within the vagina the straight portion extends in direction towards the user's torso. In this manner, a user may comfortably insert the distal tip 16 of the device into her vagina while in the supine position. Moreover, once the distal tip 16 is inserted within the vagina, a user can easily grasp the substantially straight portion 14 while in the supine position to thereby enable manual self-manipulation of the device.

Please make the following amendment to paragraph 3 on page 6, line 11:

The clitoral stimulation cup portion 18 is preferably mounted to the straight portion 14 such that its vertical position on the straight portion 14 may be selectively adjusted by the user. For example, the straight portion 14 could be provided ~~with~~ with a slotted groove having a plurality of slots or the like and the clitoral stimulation cup portion 18 could be provided a post which extends from a rear surface of the clitoral stimulation cup portion 18, the post being structured and arranged to be inserted into one of the slots in the slotted groove. In this manner, the user could selectively position the clitoral stimulation cup portion 18 as desired.

Please make the following amendment to the Abstract on page 12:

A sexual aid device comprising a curved portion having a proximal and a distal end, a substantially straight portion, the straight portion extending from the proximal end of the curved portion thereby forming an approximate J shape, and ~~mechanical means~~ a rod and an electric motor for causing movement of the curved portion is provided. The movement can be arcuate, circular, vibratory, an extending movement or a “come hither” back-and-forth movement. The distal end of the curved portion stimulates a female’s Grafenberg spot or G spot when the device is inserted into the vagina with the straight portion pointing away from the curved portion towards the female’s torso. The straight portion extends coextensively from the curved portion. The device also includes a clitoral stimulation portion which is textured and vibrates.